

# BULLCASTER

Foshan Bullcaster Co.,Ltd



**FURNITURER CASTER**









# Eternity



Chrome-plated bracket, aluminum core PP single wheel,  
There is no brake, different sizes, 40.50.60mm, you can choose  
You can choose 56x36mm flat size, and M10x20mm screw

Optional accessories and corresponding installation height

					
40mm	32mm	71mm	56x36mm	M10x20	M10x20
50mm	35mm	78.5mm	56x36mm	M10x20	M10x20
60mm	35mm	89.5mm	56x36mm	M10x20	M10x20



# Passion



Brake



Activity



Double ball bearing



No trace








Mute



Environmental friendly



Optional accessories and corresponding installation height



50mm

24mm

67mm

/

M10x20

M11x22

65mm

24mm

82mm

/

M10x20

M11x22

75mm

24mm

95mm

/

M10x20

M11x22

100mm

24mm

110mm

/

M10x20

M11x22

Multiple colors for single wheel:





# Smile



Nylon bracket, transparent double roller, plunger specification: M11X22  
This caster has no bearing, but can be made with bearing  
You can also choose M10x20mm screw



Brake



Activity



No trace




Mute




Environmental friendly

Optional accessories and corresponding installation height




50mm




35mm




78.5mm



56x36mm



M10x20



M11x22



# Hope



Aluminum alloy bracket, nylon double wheel aluminum side cover,  
Activity method: activity, brake, installation method: flat plate, screw rod, plunger  
You can choose M11x22mm plunger and M10x20mm screw



Brake



Activity



Shaft sleeve



No trace




Mute




Environmental friendly

Optional accessories and corresponding installation height




40mm




46mm




56mm



38x38mm  
25x25mm



M10x20



M10x20

50mm

55mm

67mm

47x47mm  
34x34mm

M10x20

M10x20



Business office chair



# Cosy



Nylon bracket, PU wheel surface, PP inner,  
Activity method: activity, brake, installation method: screw rod, plunger  
You can choose M11x22mm plunger and M10x20mm screw



Brake



Activity



No trace




Mute




Environmental friendly

Optional accessories and corresponding installation height




50mm




35mm




78.5mm



/



M10x20



M11x22



# Grace



Nylon bracket, PVC wrap, PP side wheel, double wheel structure  
 Activity method: activity, brake, installation method: screw rod, plunger  
 You can choose M10x20mm screw M11x22mm plunger



Brake



Activity



No trace




Mute



Environmental friendly

Optional accessories and corresponding installation height




75mm




22mm




95.5mm



/



M10x20



M11x22



12:12

# Rainbow



Aluminum alloy bracket, PU side wheel, double wheel structure, hollow side cover design

Activity method: activity, brake, installation method: screw rod, plunger

You can choose M11x22mm plunger and M10x20mm screw



Brake



Activity



Double ball bearing



No trace




Mute




Environmental friendly

Optional accessories and corresponding installation height




60mm




35mm




89.5mm



56x36mm



M10x20



M11x22



# Lullably



Nylon bracket, dust-proof roof, PA side wheel, wheel bread PU, stable double wheel structure  
 Activity method: activity, brake, installation method: flat plate, screw rod, plunger  
 You can choose M10x20mm screw rod or M11X22mm plunger



Brake



Activity



No trace




Mute




Environmental friendly

Optional accessories and corresponding installation height




30mm




35mm




39mm



30x30mm  
20x20mm



M10x20



M11x22

40mm

40mm

48mm

30x30mm  
20x20mm

M10x20

M11x22

50mm

52mm

63mm

30x30mm  
20x20mm

M10x20

M11x22





# Bliss



Black paint bracket, PU single wheel, double ball bearing,  
Activity method: activity, brake, installation method: flat plate, screw rod, plunger  
You can choose M11x22mm plunger and M10x20mm screw



Brake



Activity



Double ball bearing



No trace




Mute



Environmental friendly

Optional accessories and corresponding installation height




40mm




20mm




59mm



60x44mm  
44x30mm



M12x25



M11x22

50mm

24mm

72mm

70x52mm  
52x35mm

M12x25

M11x22



# Freedom



Chrome-plated bracket, TPE single wheel, dustproof PP side cover  
 Activity method: activity, brake, installation method: flat plate, screw rod, plunger  
 You can choose M11x22mm plunger and M10x20mm screw



Brake



Activity



Double ball bearing








No trace



Mute



Environmental friendly



25mm

13mm

37.5mm

39x33mm  
30x24mm

M10x20

M10x20

32mm

13mm

44.5mm

39x33mm  
30x24mm

M10x20

M10x20

35mm

17mm

52mm

46x38mm  
36x28mm

M10x20

M10x20

50mm

17mm

65mm

46x38mm  
36x28mm

M10x20

M10x20

50mm

23mm

73mm

46x38mm  
36x28mm

M10x20

M10x20

65mm

23mm

87mm

46x38mm  
36x28mm

M10x20

M10x20

75mm

23mm

99mm

46x38mm  
36x28mm

M10x20

M10x20



# Peace



Galvanized bracket, PA single wheel,  
 Installation method: flat plate, screw rod, plunger, movable method: fixed, movable, brake, side brake  
 You can choose 56x36mm flat size, and M10x20mm screw



Brake



Activity



No trace








Mute



Environmental friendly

Optional accessories and corresponding installation height



25mm	12mm	35mm	38x32mm 30x24mm	M10x15	M11x22
40mm	15mm	50mm	46x38mm 36x28mm	M10x15	M11x22
50mm	20mm	65mm	59x47mm 46x35mm	M10x15	M11x22
65mm	27mm	84mm	70x58mm 55x42mm	M10x15	M11x22
75mm	27mm	93mm	70x58mm 55x42mm	M10x15	M11x22



# If



Galvanized bracket, rubber wheel

Activity method: activity, brake, installation method: flat plate, screw rod, plunger  
 You can choose M10x20mm screw rod and M11x22mm plunger



Brake



Activity



No trace







Mute



Environmental friendly

Optional accessories and corresponding installation height



25mm	12mm	35mm	38x32mm 30x24mm	M10x20	M11x22
40mm	17mm	50mm	46x38mm 36x28mm	M10x20	M11x22
50mm	20mm	65mm	59x47mm 46x35mm	M10x20	M11x22
65mm	27mm	84mm	70x58mm 55x42mm	M10x20	M11x22
75mm	27mm	93mm	70x58mm 55x42mm	M10x20	M11x22





# Renaissance



Copper-plated bracket, optional zinc-plated, bronze, red bronze and other PP spherical rollers  
 Activity method: activity, brake, installation method: flat plate, screw rod, plunger



Brake



Activity




No trace




Mute



Environmental friendly




40mm



33mm




50mm



38x38mm  
27x27mm



M10x15



M11x22

50mm

45mm

64mm

38x38mm  
27x27mm

M10x15

M11x22



# Bubble



Galvanized bracket, transparent PU wheel

Activity method: activity, brake, installation method: flat plate, screw rod, plunger

The single wheel color can also have a variety of colors to choose from: white, brown, blue, yellow, etc.

You can choose M10x20mm screw rod, M11x22mm plunger



Brake



Activity



No trace







Mute



Environmental friendly

Optional accessories and corresponding installation height



40mm

20mm

50mm

42x42mm  
32x32mm

M10x20

M11x22

50mm

24mm

65mm

42x42mm  
32x32mm

M10x20

M11x22

75mm

24mm

95mm

60x60mm  
44x44mm

M10x20

M11x22



# Root



Fixed feet, galvanized bracket, non-slip rubber base  
 Can be made of stainless steel, color-plated zinc and other materials. The normal size is 50mm,  
 Please consult us if you need other sizes.



40mm	32mm	71mm	56x36mm	M10x20	M10x20
50mm	35mm	78.5mm	56x36mm	M10x20	M10x20
60mm	35mm	89.5mm	56x36mm	M10x20	M10x20







[Bullcaster.com](http://Bullcaster.com)

Tel: +8615813668894

WhatsApp: +8615813668894

Email: [info@bullcaster.com](mailto:info@bullcaster.com)

Add: Foshan City, China